


OPTICAL FIBRE ASSEMBLIES

Patchcords Duplex Patchcords - Singlemode

OS1



Features & Specifications


- ▶ Standard product manufactured on 2.8mm (nominal dia.) LSZH zip cable. Also available in 2mm (nominal dia) cable
- ▶ Individual test sheet and unique product identification number for traceability
- ▶ Available in SC, ST, FC, LC, E2000 & MU connector styles
- ▶ Low insertion loss (<0.3dB) & high return loss (>50dB)
- ▶ RoHS compliant

Technical Specifications

TEST	METHOD	SPECIFICATION
Connector Type Standards	IEC61574 series	-
Insertion Loss	IEC 61300-3-4	<0.30dB
Flammability	IEC60332-1	-
Singlemode Return Loss UPC	IEC61300-3-6	>50dB

ASSEMBLY SPECIFICATION	
Length of assembly	Tolerance
Less than 0.5m	-0/+0.10m
Between 0.5m and 5m	-0/+0.15m
Greater than 5m	-0/+0.20m

Part Number



*Note: these are new products, please call sales for more details

- 1 Other connectors available upon request.
- 2 MTRJ is available in MiniZip only.
- 3 Other colour options available for singlemode and multimode cable.
- 4 Other lengths available upon request.